

YOUR SOLUTION FOR HEATING BATHROOM & DHW



2016 - 2017

Confort et économies d'énergie

Founded in 1956




RESIDENTIAL

Heaters, radiant panels, convectors.




BATHROOM AND KITCHEN



PATIO HEATERS



BOILERS, DHW, WATER HEAT PUMP



SMART HEATING



Premier sas radiant panel

Electronic controls with digital display
All aluminum heating element - All steel body

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
500	50,0 x 45,0 x 73,0	3,9	PREMIER 500W	A691491
1000	60,0 x 45,0 x 9,3	4,9	PREMIER 1000W	A691493
1500	80,0 x 45,0 x 9,3	5,8	PREMIER 1500W	A691495
2000	100,0 x 45,0 x 9,3	7,8	PREMIER 2000W	A691497

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth 22 mm with wall mounting bracket
White color (RAL 9016)

Aixance SMART ECOcontrol® radiant panel

Electronic or digital controls
All aluminum heating element - All steel body
Programmable through optional cassettes

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
300	45,2 x 44,0 x 11,3	3,8	AIXANCE 300W	A692700
500	53,2 x 44,0 x 11,3	4,4	AIXANCE 500W	A692701
750	53,2 x 44,0 x 11,3	4,4	AIXANCE 750W	A692702
1000	63,7 x 44,0 x 11,3	5,3	AIXANCE 1000W	A692703
1250	74,2 x 44,0 x 11,3	6,1	AIXANCE 1250W	A692704
1500	84,7 x 44,0 x 11,3	5,5	AIXANCE 2000W	A692705
2000	105,7 x 44,0 x 11,3	7,1	AIXANCE 2500W	A692707

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth 22 mm with wall mounting bracket
White color (RAL 9016)

Tactic natural convection heater

Electronic thermostat
All aluminum heating element - All steel body
150 cm power cord + Euro plug - Mobile with optional Caster kit

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
500	36,0 x 40,0 x 8,0	3,0	TACTIC 500W	A692881
750	36,0 x 40,0 x 8,0	3,7	TACTIC 750W	A692882
1000	44,0 x 40,0 x 8,0	4,1	TACTIC 1000W	A692883
1500	52,0 x 40,0 x 8,0	5,0	TACTIC 1500W	A692885
2000	60,0 x 40,0 x 8,0	5,5	TACTIC 2000W	A692887
2500	76,0 x 40,0 x 8,0	7,1	TACTIC 2500W	A692888
Casters kit (x20)	23,5 x 12,0 x 5,0	0,75	2 feet + 4 wheel	A691600

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth 22 mm with wall mounting bracket
White color (RAL 9016)

Basic natural convection heater

Mechanical thermostat
All steel body - Sheathed heating element with aluminum fins,
150 cm power cord + Euro plug - Mobile with optional Caster kit

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
500	36,0 x 40,0 x 8,0	3,0	BASIC 500W	A692861
750	36,0 x 40,0 x 8,0	3,7	BASIC 750W	A692862
1000	44,0 x 40,0 x 8,0	4,1	BASIC 1000W	A692863
1500	52,0 x 40,0 x 8,0	5,0	BASIC 1500W	A692865
2000	60,0 x 40,0 x 8,0	5,5	BASIC 2000W	A692867
2500	76,0 x 40,0 x 8,0	7,1	BASIC 2500W	A692868
3000	84,0 x 40,0 x 8,0	7,9	BASIC 3000W	A692869
Casters kit (x20)	23,5 x 12,0 x 5,0	0,75	2 feet + 4 wheels	A691600

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth 22 mm with wall mounting bracket
White color (RAL 9016)



PREMIER SAS



AIXANCE SMART ECOcontrol®



TACTIC



BASIC



Glassance combined convection / radiant heater

White or dark brown
Fine tuning electronic thermostat.

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
1000	60,0 x 48,0 x 10,9	7,9	BROWN 1000W	A689883
1500	80,7 x 48,0 x 10,9	10,2	BROWN 1500W	A689885
2000	100,0 x 48,0 x 10,9	13,0	BROWN 2000W	A689887
1000	60,0 x 48,0 x 10,9	7,9	WHITE 1000W	A689963
1500	80,7 x 48,0 x 10,9	10,2	WHITE 1500W	A689965
2000	100,0 x 48,0 x 10,9	13,0	WHITE 2000W	A689967

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth with wall mounting bracket



GLASSANCE



BATHROOM AND KITCHEN

Bahia heater and towel dryer

Electronic controls

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
500	50,0 x 91,4 x 10,0	11,2	BAHIA 500W	A690671
750	50,0 x 127,4 x 10,0	15,6	BAHIA 750W	A690672
1500	60,0 x 151,4 x 10,0	17,9	BAHIA 1000W	A690673

CLASS 2 - IP44 - CE (EN/IEC 60335-1-2010)

*Additional depth with wall mounting bracket
White color



BAHIA

Bahia Eole heater and towel dryer fan boost

Infrared remote control

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
500 + 1000	50,0 x 101,1 x 13,0	14,0	EOLE 1500W	A691655
750 + 1000	50,0 x 137,1 x 13,0	19,0	EOLE 1750W	A691656
1000 + 1000	60,0 x 161,1 x 13,0	24,5	EOLE 2000W	A691657

CLASS 2 - IP44 - CE (EN/IEC 60335-1-2010)

*Additional depth with wall mounting bracket
White color



BAHIA EOLE

Indigo compact heater and towel dryer

Electronic controls - All steel body
Natural convection heater + Fan boost
Rating 600W convection + 800W ventilation

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
600 + 800	35,5 x 67,0 x 15,5	7,6	INDIGO 1400W	A690465

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth with wall mounting bracket
White color



INDIGO
BATHROOM & KITCHEN



PATIO HEATER


IRC design patio heater

Short wave infrared heater (covers 10/12m²)
Heats outside terraces and balconies
Steel body and stainless steel grid - Halogen HeleN lamp

RATING (W)	DIMENSIONS W X H X D* (CM)	WEIGHT (KG)	MODEL	ITEM N°
1500	50 x 14,1 x 8,5	2,3	IRC 1500W	A692625

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

*Additional depth with wall mounting bracket
White color




IRC DESIGN

Gialix electric boiler

Cast iron heat exchanger



GIALIX

 MODEL	DIMENSIONS	RATING	TENSION V	WEIGHT (KG)	ITEM N°
Gialix BC 6 MT Mono 230	340 x 500 x 280	0 to 6	Mono 230	20	A693090
Gialix BC 12 MT Mono 230	340 x 500 x 280	0 to 12	Mono 230	25	A693091
Gialix BC 12 MT Tri 400	340 x 500 x 280	0 to 12	Tri 400	25	A693092
Gialix BC 16 MT Tri 400	340 x 500 x 280	0 to 16	Tri 400	25	A693093
Gialix BC 6 MT Confort Mono 230	340 x 500 x 280	0 to 6	Mono 230	20	A693094
Gialix BC 12 MT Confort Mono 230	340 x 500 x 280	0 to 12	Mono 230	25	A693095
Gialix BC 12 MT Confort Tri 400	340 x 500 x 280	0 to 12	Tri 400	25	A693096
Gialix BC 16 MT Confort Tri 400	340 x 500 x 280	0 to 16	Tri 400	25	A693097
Gialix BC 24 MA Confort Tri 400	405 x 620 x 280	2-8-12-16-20-24	Tri 400	42	A693098
For higher rating 36 to 196 kW					ASK

CLASS 2 - IP24 - CE (EN/IEC 60335-1-2010)

Xiros range

TANK SIZE	DIAMETER	HEIGHT	WEIGHT (KG)	ITEM N°
Xiros 100 liters				
100	500	1270	55	A692463
Xiros 150 liters				
150	500	1640	75	A692465

XYROS AIR

- COP EN16147 = 2,3 (EN255-3 = 3,3)
- Unique concentric air duct
- 450 L with only 250w electricity
- Up to 70% energy savings

XYROS WATER

- Connected to floor heating return flow.
- COP EN16147 = 4,1
- Up to 75% energy savings
- Low energy circulation pump included

COMMON CHARACTERISTICS

- Smart, easy to use controls
- Works from -7°C to +35°C.
- Offering 60° C water temperature.
- 1200W backup element
- Legionela protection
- Wall or tripod mount

Aireo range

TANK SIZE	DIAMETER	HEIGHT	WEIGHT (KG)	ITEM N°
200	630	1426	65	A693167
270	630	1690	75	ASK

AIREO AIR

- Air source type
- COP EN16147 = 2,3 (EN255-3 = 3,3)
- Up to 80% energy savings
- Stainless steel water tank
- Refrigerant. Propan R290

AIREO WATER

- Connected to floor heating return flow.
- COP EN16147 = 3,8
- Up to 80% energy savings
- Stainless steel water tank
- Low energy circulation pump included
- Refrigerant. Propan R290

COMMON CHARACTERISTICS

- Smart, easy to use controls
- Works from -7°C to +35°C.
- Offering 60° C water temperature.
- 1500W backup element
- Legionela protection
- Free floor standing

Released in 2016 - 2017 : 150 L - 100 L - 80 L - 50 L tank models



XIROS



AIREO

YOUR DISTRIBUTOR:

